



S.C.P. s.a.

Suministros de Conectores Profesionales, s.a.

M8171417-D33

M81714/17 High Density Modules Series I Size 22D Class D

Terminal Junction Modules



Operating Range

Temperature:
 -65°C to 200°C
Insulation Resistance:
 5000 Megaohms @ 25°C
Dielectric Withstanding Voltage:
 1000 VRMS at Sea Level
 200 VRMS at 110,000 ft.
Current Rating
 5 Amps
Vibration & Shock:
 MIL-T-81714 Paragraph
 3.5.5 and 3.5.8

Materials

Module Body:
 Polyetherimide per ASTM-D5205
Grommet:
 Silicone Blend Elastomer per A-A-59588
Contact Retainers:
 Stainless Steel
Internal Socket Contacts:
 Copper Alloy, Hard Gold Plated in
 Accordance with MIL-G-45204
Accepts Multiple Wire Sizes:
 Size 22, 26 AWG

Bussing Configurations	Feedback	
	Military P/N	APCD P/N
	M81714/17-D30	TJHD22700
	M81714/17-D31	TJHD22701
	M81714/17-D32	TJHD22702
	M81714/17-D33	TJHD22703
	M81714/17-D34	TJHD22704
	M81714/17-D35	TJHD22705
	M81714/17-D36	TJHD22706
	M81714/17-D37	TJHD22707


Bussing Configurations	Feedback	
	Military P/N	APCD P/N
	M81714/17-D38	TJHD22708
	M81714/17-D39	TJHD22709
	M81714/17-D40	TJHD22710
	M81714/17-D42	TJHD22712
	M81714/17-D43	TJHD22713
	M81714/17-D44	TJHD22714
	M81714/17-D45	TJHD22715

Contacts Supplied: M39029/1-507 Qty 22




Terminal Junction Module Dimensions

Feedback Dimensions



Bussing Configuration



Contacts Supplied: M39029/1-507
Quantity Supplied: 22

0

Tel.: +34 91 355 60 06
e-mail: comercial@scp-sa.es